

## Product Data



INTERSPERSAL

# SperseStab™-4008 UV Stabilizer / Synergist

### Overview

SperseStab 4008 is a highly effective light stabilizer and synergist for use in various plastics including: polyolefins, TPO, TPE, PVC, PUR, adhesives, wax and oils. Used in combination with UV Absorbers and Hindered amine light stabilizers the SperseStab 4008 provides a synergistic effect. As a UV resistant thermal stabilizer SperseStab 4008 substantially increases the long term heat aging of polymers with minimal colorbody formation.

### Chemistry

Chemical Name:	Proprietary
CAS Number:	Proprietary
Chemical Structure:	Proprietary

### Typical Properties

Product Form:	Solid
Melting Range:	55-65°C
Color:	white powder
Density(20°C):	1.03 g/cm <sup>3</sup>

### Advantages

- Strong synergism with Hindered Amines
- greatly improves long term thermal aging with decreased colorbody formation associated with typical phenolic antioxidants
- FDA cleared in polyolefins

### Storage

This product may be stored up to two years in a sealed container. Containers should be kept tightly closed when not in use and stored in a cool, dry place.

## Safety

Please consult the Safety Data Sheet (SDS) prior to handling or using this product.

## FDA Regulations

Cleared under 21 CFR §178.2010 for use in olefin polymers. Consult your Interspersal Inc. representative for the most updated details, including restrictions of use.

## Important notice

The information and statements herein are believed to be reliable but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.

Interspersal Inc  
[www.interspersal.com](http://www.interspersal.com)  
+1 (724) 485-9350